

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Version 1

Revision: 28.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** INSEBO PU-Universal-Reiniger**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture** Removes uncured PU foam residues**1.3 Details of the supplier of the safety data sheet**

WS INSEBO GmbH

Industriestraße 24, A-2325 Himberg bei Wien

Tel.: +43 (0) 2235/86227-0

Fax: +43 (0) 2235/86020

e-mail: office@insebo.com

1.4 Emergency telephone number: Call local emergency information.**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07

Signal word Danger**Hazard-determining components of labelling:**

ethyl acetate

acetone

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with national regulations.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 1)

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards
Results of PBT and vPvB assessment

This mixture does not meet the PBT- or vPvB-criteria according to Regulation (EC) No 1907/2006.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	40-65%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-45%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0	isobutane (< 0,1 % butadiene) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	3-10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures



First aid

4.1 Description of first aid measures
General information:

In case of accident or if you feel unwell seek medical advice (show label where possible).

In case of unconsciousness place patient stably in side position for transportation.

Never give anything by mouth to an unconscious person.

After inhalation: Supply fresh air, keep warm and at rest. If symptoms persist seek medical advice.

After skin contact:

Remove contaminated clothes. Wash affected skin thoroughly with water and soap.

In case of irritation seek medical treatment.

After eye contact:

Remove contact lenses and rinse opened eyes for at least 15 minutes with plenty of water. If irritation persists seek medical advice.

After swallowing:

Swallowing impossible when used as recommended.

Flush with copious amounts of water (only if person is not unconscious).

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 2)

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

In case of inhalation: causes headache, drowsiness, dizziness, nausea, can cause unconsciousness.

After skin contact: frequently or prolonged skin contact may cause dermal irritation; degreases and dries skin.

After eye contact: irritation (redness, burning)

After ingestion: causes nausea, depression; may have an impact on the central nervous system.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment (decontamination, vital function), there is no specific antidote.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: CO₂, extinguishing powder, sand, soil

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Product contains highly flammable vapours and liquids. Formation of smoke in case of fire; carbon oxides, soot, hydrocarbons and aldehydes can be released due to incomplete combustion and thermolysis.

Risk of bursting due to heat. Formation of explosive air/vapour mixtures are possible. Vapors are heavier than air. By distribution at ground level flash back to distant ignition sources is possible.

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.

In the case of fire wear self-contained respiratory equipment and full protective suit.

Additional information

Cool endangered receptacles with water spray. Contain runoff to prevent entry into water or drainage systems.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Please notice instructions for person-related safety precautions, wear protective equipment (see 8.)

Avoid inhalation and contact with skin and eyes.

Do not breathe spray.

Ensure adequate ventilation.

Remove ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Contain the spilled material by bunding.

Advise water authority in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with noncombustible absorbent material, (eg sand, diatomite, vermiculite).

Collect for recovery or disposal in suitable receptacles.

Clean affected area with plenty of water and detergent. Collect rinse water in labelled salvage container for disposal according to the regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See section 13 for disposal information.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

While handling pay attention to the usually precaution for chemicals.
Comply with instructions for use.
Use only in well ventilated areas.
Do not breathe fumes/aerosol.
Avoid contact with the eyes and skin.
Wash hands before break and at the end of work.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
Use only non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store in original container only in a well-ventilated, cool, dry, secure area.
Storage regulations for pressurized gas receptacles must be observed.

Information about storage in one common storage facility:

Do not store food, beverages and animal feeding stuffs in the storage area.
Store away from oxidizing and self-igniting materials.

Further information about storage conditions:

Keep out of the reach of children and domestic animals.
Protect from heat and direct sunlight.

7.3 Specific end use(s) Use according to instructions.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: Provide good ventilation or exhaust at work.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 141-78-6 ethyl acetate

IOELV (EU)	Short-term value: 1468 mg/m ³ , 400 ppm; Long-term value: 734 mg/m ³ , 200 ppm
MAK (Austria)	Short-term value: 1468 mg/m ³ , 400 ppm; Long-term value: 734 mg/m ³ , 200 ppm
AGW (Germany)	Long-term value: 730 mg/m ³ , 200 ppm; 2(I);DFG, EU, Y

CAS: 67-64-1 acetone

IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
MAK (Austria)	Short-term value: 4800 mg/m ³ , 2000 ppm; Long-term value: 1200 mg/m ³ , 500 ppm
AGW (Germany)	Long-term value: 1200 mg/m ³ , 500 ppm; 2(I);AGS, DFG, EU, Y

CAS: 75-28-5 isobutane (< 0,1 % butadiene)

MAK (Austria)	Short-term value: 3800 mg/m ³ , 1600 ppm; Long-term value: 1900 mg/m ³ , 800 ppm
AGW (Germany)	Long-term value: 2400 mg/m ³ , 1000 ppm; 4(II);DFG

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 4)

CAS: 74-98-6 propane

MAK (Austria)	Short-term value: 3600 mg/m ³ , 2000 ppm; Long-term value: 1800 mg/m ³ , 1000 ppm
AGW (Germany)	Long-term value: 1800 mg/m ³ , 1000 ppm; 4(II);DFG

CAS: 106-97-8 butane, pure

MAK (Austria)	Short-term value: 3800 mg/m ³ , 1600 ppm; Long-term value: 1900 mg/m ³ , 800 ppm
AGW (Germany)	Long-term value: 2400 mg/m ³ , 1000 ppm; 4(II);DFG

Regulatory information

IOELV (EU): (EU) 2017/164

MAK (Austria): GKV 2018, 254. Verordnung, 24.9.2018, Teil II

AGW (Germany): TRGS 900

DNELs:

ethyl acetate (CAS 141-78-6)

workers

short-term exposure, local effects, inhalation: 1468 mg/m³

long-term exposure, lokale Effekte, inhalation: 734 mg/m³

long-term exposure, systemic effectse, dermal: 63 mg/kg bw/day

costumers

short-term exposure, local effects, inhalation: 734 mg/m³

long-term exposure, local effects, inhalation: 367 mg/m³

long-term exposure, systemic effects, dermal: 37 mg/kg bw/day

long-term exposure, systemic effects, oral: 4.5 mg/kg bw/day

acetone (CAS 67-64-1)

workers

long-term exposure, systemic effects, inhalation 1210 mg/m³

short-term exposure, local effects, inhalation 2420 mg/m³

long-term exposure, systemic effects, dermal 186 mg/kg bw/day

costumers

long-term exposure, systemic effects, inhalation 200 mg/m³

long-term exposure, systemic effects, dermal, oral 62 mg/kg bw/day

PNECs:

ethyl acetate (CAS 141-78-6)

freshwater 0.26 mg/l, marine water 0.026 mg/l

sediment freshwater 0.34 mg/kg, marine water 0.034 mg/kg

soil 0.22 mg/kg

acetone (CAS 67-64-1)

freshwater 10.6 mg/l, marine water 1.06 mg/l

sediment freshwater 30.4 mg/kg, marine water 3.04 mg/kg

intermittent releases 21 mg/l; STP 19.5 mg/l; soil 0.112 mg/kg

Additional information: Based on actual legally binding lists.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures:

Avoid unnecessary contact with the product. Do not eat, drink or smoke at workplace and keep it tidy.

Do not inhale gases / fumes / aerosols.

Remove contaminated clothing and wash carefully before reuse.

Store protective clothing separately.

Pregnant women should strictly avoid inhalation or skin contact.

Wash hands before break and at the end of work.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 5)

Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators (EN 141, Filtre type A).

Protection of hands:



Chemical resistant gloves (EN 374)

Dispose of when contaminated inside, when perforated or when contamination outside cannot be removed.

Material of gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses with side shields (EN 166)

Ensure eye bath is to hand.

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Form:	Liquid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined

pH: Not applicable

Change in condition

Melting point/freezing point:	Not available
Boiling point/boiling range:	No data available

Flash point:	No data available
Flammability (solid, gas):	No data available.

Ignition temperature:	> 350 °C (propellant)
Decomposition temperature:	No data available.
Auto-ignition temperature:	No data available.

Explosive properties:	No data available
Explosion limits:	
Lower:	1.5 Vol % (propellant)
Upper:	16 Vol % (propellant)
Oxidising properties:	No data available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 6)

Vapour pressure:	< 0.7 MPa
Density at 20 °C:	≈ 0.8 g/cm ³
Solubility in / Miscibility with water:	Partly soluble.
Partition coefficient: n-octanol/water:	No data available.
Viscosity	
Dynamic:	No data available.
VOC (EC):	0.998 kg/kg
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity Stable under recommended transport or storage conditions.

10.2 Chemical stability No hazardous reaction when handled and stored according to provisions.

10.3 Possibility of hazardous reactions

Danger of receptacles bursting because of high vapour pressure when heated.
 Exothermic reaction with strong acids.

10.4 Conditions to avoid

Heat, open flames, static electricity, under standard conditions of use hazardous reactions are not known.

10.5 Incompatible materials: Strong acids and oxidizing agents

10.6 Hazardous decomposition products:

Formation of smoke in case of fire; carbon oxides, soot, hydrocarbons and aldehydes can be released due to incomplete combustion and thermolysis.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

There are no product specific data on toxicology available.

CAS: 141-78-6 ethyl acetate

Oral	LD50	4934 mg/kg (rabbit)
Dermal	LD50	> 20 g/kg (rabbit)
Inhalative	LD50/2h	29.3 mg/l (rat)

CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LC50/4h	76 mg/l

Primary irritant effect:

Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Experience with humans:

In case of inhalation: causes headache, drowsiness, dizziness, nausea, can cause unconsciousness.

After skin contact: frequently or prolonged skin contact may cause dermal irritation; degreases and dries skin.

After eye contact: irritation (redness, burning)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 7)

After ingestion: causes nausea, depression; may have an impact on the central nervous system.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

For the product there are no ecotoxicological data available.

CAS: 141-78-6 ethyl acetate

EC50/48h	5600 mg/l (alga, <i>Desmodesmus subspicatus</i>) 610 mg/l (water flea, <i>Daphnia magna</i>)
LC50/96h	230 mg/l (flathead minnow, <i>Pimephales promelas</i>)
NOEC/21d	2.4 mg/l (water flea, <i>Daphnia magna</i>) (OECD 211)
NOEC/32d	> 9.65 mg/l (flathead minnow, <i>Pimephales promelas</i>)

CAS: 67-64-1 acetone

LC50/48h	8800 mg/l (water flea, <i>Daphnia magna</i>)
LC50/96h	5540 mg/l (rainbow trout, <i>Oncorhynchus mykiss</i>)

12.2 Persistence and degradability biodegradable

12.3 Bioaccumulative potential The product has a low potential for bioaccumulation.

12.4 Mobility in soil High mobility

12.5 Results of PBT and vPvB assessment Not applicable.

12.6 Other adverse effects Avoid release to the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Do not dispose waste or remains together with domestic waste, do not empty into sink or toilet, hand over to hazardous waste disposers.

European waste catalogue

16 05 04: Gases in pressure containers (including halons) containing dangerous substances

15 01 10: Packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Containers not emptied completely have to be disposed of as hazardous waste and not together with household waste.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

Do not pierce or burn, even after use.

(Contd. of page 8)

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR
IMDG
IATA

1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR



Class
Label
IMDG, IATA

2 5F Gases.
2.1



Class
Label

2.1
2.1

14.4 Packing group
ADR, IMDG, IATA

Void

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user
Danger code (Kemler):

Warning: Gases.

-

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

UN "Model Regulation":

UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations: -

Waterhazard class:

Water hazard class (German Regulation) 1 (Self-assessment): slightly hazardous for water.

VOC (EC): 0.998 kg/kg

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2021

Revision: 28.06.2021

Trade name: INSEBO PU-Universal-Reiniger

(Contd. of page 9)

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Further information:

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008: Calculation method

Abbreviations and acronyms:

- CLP: REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- EINECS: European Inventory of Existing Commercial Chemical Substances
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- AGW: occupational exposure limit, Germany
- IOELV: Indicative Occupational Exposure Limit Values (EU)
- MAK: maximum concentration of a chemical substance in the workplace, Austria
- LC50: lethal concentration, 50 percent
- LD50: lethal dose, 50 percent
- EC50: maximal effective concentration, 50 percent
- NOEL/NOEC: No Observed Effect Concentration
- PBT: persistent, bioaccumulative and toxic properties
- vPvB: very persistent and very bioaccumulative properties
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- VOC: Volatile Organic Compounds
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Data compared to the previous version altered -