

Antik Kitt

Product Description

Solvent-free one-component putty based on hybrid polymer. Vulcanizes under the influence of moisture to form a permanently elastic putty.

Product Properties

- very low emission - EMICODE EC1^{Plus}
- Shrinkage and solvent-free
- UV, aging and weather resistant
- Silicone-free for a clean and high-quality surface
- very high flow resistance
- high initial adhesion
- very broad adhesive range
- no uprise behavior, therefore no need to weigh down/fix the components
- very good adhesion on almost all substrates
- paintable
- vibration-dampening
- ready-to-use
- not corrosive to metals
- for waterproof bonds
- suitable for indoor and outdoor use
- gluing and sealing with the same product
- can be applied on moist substrates
- water resistant
- temperature resistant from -20 °C to +90 °C
- almost odorless
- phthalate-free
- isocyanate-free
- halogen-free

Areas of Application

The Antik Kitt is designed for reglazing sash and composite windows. Due to its specially adjusted viscosity, the Antik Kitt is excellent for modeling putty beads.

Historical buildings and residential houses, listed buildings, museums, churches and monasteries, and cultural institutions

Wood construction, repair and touch-up work, roofing, floor coverings and skirting boards, doors, glass mosaic, metal construction.

Form of Delivery

Cartridge: 290 ml
Packing unit: 20 pieces per box

Substrates

Suitable substrates:

plaster, concrete, aerated concrete, mortar, masonry, brick, clinker, cement, fiber cement, plasterboard, wood, wood chipboard, lacquered, glazed or impregnated wood, wood fiber boards, aluminum, corrosion-protected metals, copper, zinc, ceramics, tiles, enamel, stoneware, polystyrene, glass, many plastics

Conditionally suitable substrates:

tar and bituminous substrates

Unsuitable substrates:

EPDM, PIB, PTFE, PP, PE, gypsum, silicone

Instructions for Use

The adhesive surfaces must be clean, dry, free from release agents and firm. Dust, grease, oil and loose parts must be removed before processing. We advise carrying out a suitability test for the large number of substrates, building materials and/or coatings used today, especially for plastics, paintings and powder coatings. Tar and bitumen-containing substrates can lead to color changes of the mass and affect the adhesion.

Cut off the cartridge nipple with a sharp knife. Screw the nozzle onto the cartridge and cut it to the desired bead width (angled). Hardened Antik Kitt can only be removed mechanically or with solvents.

It is necessary to check whether a paint applied subsequently to the Antik Kitt is compatible. Some paints may cause color changes in the putty and affect adhesion.

To ensure compatibility of the putty with the materials, we recommend conducting tests on small areas before application.

When processing larger quantities in enclosed spaces, ensure adequate fresh air during the curing time. Material consumption depends on the nature/roughness of the bonding surfaces/substrates. Reaction time depends on temperature and air and substrate humidity. The final strength of the putty is only achieved after several days. With above-average humidity in the substrate and/or additional moistening, curing is accelerated.

Store cartridges cool, dry, and protected from direct sunlight. Higher temperatures shorten the shelf life.

Processing tool:

We recommend using a high-quality caulking applicator with a minimum trigger ratio of 12:1, e.g. the caulking applicator of the series Irion X7-310, FX7-90, XP Delta or Except-310. Due to the viscous mass using cheap caulking applicators can cause premature muscle fatigue and damage to the tool.

Technical Data

Characteristics	Standard	Value
Density	EN 1183-1	1.5 ± 0.1 g/cm ³
Shore A hardness	EN ISO 868	approx. 60
Fire behavior	EN 13501-1	class E
Skin formation time (normal climate 23/50)		approx. 11 - 16 min
Curing (normal climate 23/50, depending on substrate)		approx. 2,5 mm/day
Temperature resistance (cured mass)		-20 to +90 °C
Processing temperature		+5 to +40 °C
Shelf life (dry, at +10 to +25 °C)		12 months

Safety Instructions

Please refer to our safety data sheet and the product label for further information on product safety and handling.

Current safety data sheets and further information on our products can be found at www.insebo.com.

Service

Upon request, our trained sales representatives are always at your disposal.

Disposal

For disposal instructions please refer to our safety data sheet and product label.

Additional Information

This technical data sheet advises without obligation and guarantee. The mentioned processing instructions have to be adapted to the prevailing conditions. The user is obliged to check the suitability and application by own experiments in order to avoid failures.

All given descriptions, data, ratios, weights, etc. can change without notice and do not represent contractually agreed properties of the product. Existing laws, standards and regulations are to be observed by the recipient of our products in their own responsibility.

Due to the large number of possible influences during processing and application, a guarantee of certain properties or suitability for a specific application can not be made, own tests are necessary.

The right to make technical changes is reserved.

GEV-EMICODE

EC1^{Plus} – very low emission

Testing institute:

GEV Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,
Klebstoffe und Bauprodukte e.V.